

# CONCRETE PAVERS NATURAL STONE

- RUST REMOVER**
- OIL & GREASE CLEANER**
- EFFLORESCENCE CLEANER**
- RUBBER, PAINT & TAR REMOVER**



- THREE FINISHES**
- WET LOOK**
- SATIN LOOK**
- NATURAL LOOK**



**Alliance** DESIGNER PRODUCTS INC.®  
WWW.ALLIANCEDP.COM

## 1 GETTING STARTED




### BEFORE YOU BEGIN PLEASE NOTE:

- 1) These products dissolve sealants.
- 2) Do not let the product dry up on concrete pavers.
- 3) Wear goggles and rubber gloves.
- 4) After using the required product on various spots. Clean the entire installation with Gator Clean Efflorescence cleaner for a uniform color.

### INSTALLATION INSTRUCTIONS:

- 1) Wet paver surface with water.
  - 2) Apply product on stain.
  - 3) Let it soak for 1-5 minutes.
  - 4) Vigorously scrub with a hard bristle brush.
  - 5) Rinse thoroughly with water.
  - 6) Repeat step 2 to 5 until the stain dissolves.
- PLEASE SEE PRODUCT LABEL FOR DETAILED INSTRUCTIONS

### CLEAN OFF THE STAINS



#### OIL & GREASE CLEANER

Gator Clean Oil & Grease Cleaner is effective in removing oil & grease from the surface of concrete pavers.

2 QT.



#### RUBBER, PAINT & TAR REMOVER

Gator Clean Rubber, Paint and Tar Remover is effective in removing rubber, paint and tar from the surface of concrete pavers.

1 QT.



#### RUST REMOVER

Gator Clean Rust Remover is effective in removing rust from the surface of concrete pavers.

2 QT.


### TOOLS REQUIRED



SPRAY NOZZLE



HARD BRISTOL BRUSH



HARD BRISTOL BROOM



PAINT TRAY



PAINT ROLLER

## 2 GET READY



### BEFORE YOU BEGIN PLEASE NOTE:

- 1) This product dissolves sealants.
- 2) Do not let product dry up on concrete paver surface.
- 3) Wear goggles and rubber gloves.
- 4) Never use on new concrete pavers. Wait at least 90 days after new pavers are installed before using this product.
- 5) In a large plastic pail dilute product with 4 parts of water to one part product, any concentration greater than this can discolor the pavers. (Choose a pail that your brush or broom will fit into.)

**IDEAL MIXTURE:** 4 parts water – 1 part product.

### INSTALLATION INSTRUCTIONS:

- 1) Wet paver surface with water.
- 2) Dip the brush or broom into the diluted product mixture in the plastic pail and apply to surface with a scrubbing motion. One gallon of the diluted mixture will do approximately 40 square feet – area covered depends on porosity of the surface being cleaned.
- 3) Scrub vigorously; work in areas of about 40 square feet at a time.
- 4) Rinse thoroughly with water and move on to the next section of 40 sq. ft.
- 5) Repeat steps 2,3,4, over all the sections in question.
- 6) Once the surface is clean, use a grass water sprinkler to keep wetting the paver surface for at least 4 hours to make sure that all the concentrate is rinsed off the paver.

### CLEAN OFF THE EFFLORESCENCE



#### EFFLORESCENCE CLEANER

Gator Clean Efflorescence Cleaner will remove any efflorescence stains trapped in the concrete paver pores. It will make the pavers look more clean and vibrant. This cleaning is ideal before a sealer is applied. The sealer will be able to get a deeper penetration into the now clean pores.

#### COVERAGE

5 US gal. MAKES 25 US gal. CLEANS APPROX. 1000 sq. ft.  
1 US gal. MAKES 5 US gal. CLEANS APPROX. 200 sq. ft.

1 US gal. or 5 US gal.



## 3 SEAL THE DEAL



### BEFORE YOU BEGIN PLEASE NOTE:

- 1) Pavers should only be sealed one year after their installation date.
- 2) Pavers MUST be 100% dry.
- 3) Paver surface temperature should be 60°F to 85°F when sealer is applied.
- 4) First clean pavers with Gator Clean products. Remove all oil, grease and rust stains. Also remove all dirt and debris.
- 5) Use Gator Clean efflorescence cleaner, to take away any trapped efflorescence in the paver.
- 6) Just use 1 layer of product because 2 layers and more might trap moisture and lead to white spots on the concrete surface.
- 7) When using Gator Seal assure yourself at least 48 hours of dry conditions prior to applying the sealer.
- 8) You can use this product once every two years for additional layers.
- 9) **COVERAGE** approx 175 sq ft per gallon

### INSTALLATION INSTRUCTIONS:

- 1) Remove all the stains from the pavers, using Gator Clean products.
- 2) Wash off the efflorescence, using the Gator Clean efflorescence cleaner.
- 3) Allow pavers to dry at least 48 hours.
- 4) Apply coat of Gator Seal using a foam roller.
- 5) Let it dry for 24 hours before using the sealed area.

### GATOR SEAL PAVER SEALANTS for CONCRETE PAVERS & NATURAL STONE

Are available in three distinct finishes. All are formulated to penetrate deep into the pores to protect and enhance the look of the Concrete Pavers and Natural Stone. Thus making the surfaces easier to clean and maintain.

#### HELPS RESIST

Salt & Calcium • Ultra Violet rays • Motor oil & grease



#### WET LOOK FINISH (HIGH GLOSS)

Gator Seal Wet Look Finish is a solvent based sealer made from acrylic polymers. Makes pavers look more vibrant. **NON SLIP FORMULA**

#### SATIN LOOK FINISH (MATT FINISH)

#### NATURAL LOOK FINISH (ENHANCES COLOR)

Gator Seal Satin and Natural Look Finishes are water based sealers made from Urathane and Elastomer polymers. **NON SLIP FORMULA**

1 US gal. or 5 US gal.



225 Bellrose West, Laval, Quebec, Canada, H7L 6A1  
Tel.: 450-624-1611 • Fax: 450-624-1622 • Toll Free: 1-866-212-1611  
www.alliancedp.com • email: info@alliancedp.com